

ancett | Intelligent Frequency Converter

F to I / F to V

DESCRIPTION

The Blancett Frequency-to-Current (F to I) and Frequency-to-Voltage (F to V) intelligent converters are state-of-the-art active sensors designed to provide enhanced features and greater flexibility for the Blancett turbine.

These microprocessor-based devices are engineered to provide an analog output directly from a Blancett turbine flow meter. The converters measure and calculate the flow rate of a turbine flow meter and produce an analog output proportional to the flow rate. The F to I and F to V converters are offered with either a 4...20 mA or a 0...5V DC output signal, enabling easy electronic integration. Choose between the capped aluminum condulet Y-enclosure (model B220-873 or B220-874) or the canister style (model B220-950 or B220-951) converters.

When a converter is ordered with a flow meter, the two components ship from the factory calibrated as a system. If the converter is a replacement, the turbine's K-Factor has changed, or the converter is being used with a different manufacturers flow meter, then re-programming is possible with an optional Windows®-based software utility. Please consult the factory for details.


FEATURES

- Converts turbine pulse output into linearized analog output
- Choice of 4...20 mA or 0...5V DC output
- Accuracy of frequency measurement is ±0.1%
- Enables integration with data acquisition devices
- Two mounting styles available for ease of installation



DIMENSIONS

Dimensions are in inches (mm).



Model B220-873 & B220-874



Model B220-950 & B220-951

SPECIFICATIONS

		F to I Models B220-873 & B220-950	F to V Models B220-874 & B220-951
Power		1030 VDC supply range Loop-powered, 6V insertion loss max	1026V DC supply range
Inputs		Magnetic Pickup	Magnetic Pickup
	Frequency	03500 Hz	03500 Hz
	Trigger Sensitivity	30 mV p-p	30 mV p-p
	Frequency Measurement Accuracy	±0.1%	±0.1%
Analog Output		420 mA current loop	05V DC
	Resolution	1:4000	1:4000
	Temperature Drift	50 ppm/°C (max)	50 ppm/°C (max)
Environmental	Ambient Temperature	–22158 °F (–3070 °C)	–22…158 °F (–30…70 °C)
Environmental	Humidity	090%, non-condensing	090%, non-condensing



MODELS

Model	Intelligent Converter	Output
B220-873	F to I	420 mA
B220-874	F to V	05V DC
B220-950	F to I	420 mA
B220-951	F to V	05V DC


Connecting Cables

Model	Length	Description
B220952-6	6 ft	5-pin cable assembly
B220952-15	15 ft	5-pin cable assemblyy

Male Connector


WIRING DIAGRAMS

F to I Converter, B220-873



4 5 0


F to V Converter, B220-874



F to I Converter, B220-950



F to V Converter, B220-951



Control. Manage. Optimize.

BLANCETT is a registered trademark of Badger Meter, Inc. Other trademarks appearing in this document are the property of their respective entities. Due to continuous research, product improvements and enhancements, Badger Meter reserves the right to change product or system specifications without notice, except to the extent an outstanding contractual obligation exists. © 2014 Badger Meter, Inc. All rights reserved.

www.badgermeter.com