



RCM Industries, Inc.

Direct Reading Flowmeters for Liquids and Gases



Product Spotlight

Flo-Gage™ Digital Display Flowmeter - RW3



Features:

- 15 Point Linearization of Flow Curve – with Interpolation
- Displays Instantaneous Flow Rate, Total & Accumulated Total
- Large 17mm (0.67") Digit for Flow Rate or Total
- Operational Temperature -30 to 80°C (-22 to 178°F)
- Rugged Enclosure IP67/NEMA 4X Rated
- Wet / Wet Differential Pressure Sensor
- Amber or Green Backlighting *Optional*
- Intrinsically Safe Approval *Optional*



www.sis-tec.com

New Digital display flow meter 2 wire loop powered 4-20mA DC transmitter features 7 digits for flow rate and 11 digits for accumulated total. On-screen engineering units are easily configured, while different units for flow rate and total can be displayed simultaneously. A wide selection of options further enhances this models capability. Optional backlighting is available for easy viewing and intrinsic safe approval for hazardous locations.

New Wet/wet differential pressure sensor is protected by an isolated stainless steel diaphragm for measuring liquids, gases and conductive flow media.

RCM has been manufacturing quality flow measuring products for over 35 years for end-users and OEM applications.

Questions or comments? E-mail us at sistec@sis-tec.com